



PC 5TX / PC 8TX Plastic ceiling loudspeakers

TECHNICAL SPECIFICATIONS



PC 5TX/ PC 8TX


PC 5TX / PC 8TX - ABS plastic ceiling loudspeakers with built-in 100V transformer with power taps.

Excellent full range sound, used where a combination of high quality background music and public address are required. These loudspeakers are designed to be quickly and simply installed into false ceilings. Wide sound dispersion and innovative neutral design makes **PC 5TX / PC 8TX** loudspeakers useful in a variety of applications, restaurants, bars, cafes, shops, offices, moles and large public spaces for background music and speech announcements. Almost the same structure and specifications as PC 5T / PC 8T, but different sound, better designed for background music use.

	PC 5TX	PC 8TX
Rated power	10 W	20 W
Transformer power taps	10 W - 5 W - 2,5 W - 1,25 W	20 W - 10 W - 5 W - 2,5 W
Sensitivity	88 dB (1 W/1 m)	89 dB (1 W/1 m)
Maximum SPL	98 dB (Pmax/1 m) at 884 Hz	102 dB (Pmax/1 m) at 5415 Hz
Frequency response	100 Hz – 20 kHz	60 Hz – 20 kHz
Dispersion at 1000 Hz	120° conical	120° conical
Driver dimensions	5" (130 mm) woofer, 0,5" (13 mm) tweeter, coaxial	8" (200 mm) woofer, 0,5" (13 mm) tweeter, coaxial
Dimensions	ø 190 mm × 80 mm	ø 274 mm × 105 mm
Weight	1,1 kg	2,1 kg
Material	Plastic	Plastic
Colour	White (RAL 9016)	White (RAL 9016)

unit: mm

PC 5TX



PC 8TX

