

### ► Features

- 12" excursion driver
- Sophisticated control electronics
- Reliable and linear operation
- Integrated M10 screw flange speaker adapter
- Two carry handles for easy transportation
- Scratch-free textured EPDM coating

### ► Applications

- High power indoor applications
- Clubs
- Theatre
- Broadcast
- PA systems



The AUDAC SX412 is a powerful tandem ported design subwoofer for indoor applications.

The results of this carefully designed and tuned subwoofer will satisfy the most demands for high power, low frequency performance at exceptionally low distortion levels.

This single 12 inch subwoofer is good for 300 Watt RMS power, 96 dB SPL sensitivity, and is capable of a maximum SPL of 121 dB SPL.

It has a flat Frequency response between 45 – 250 Hz, with a slight boost on 50 Hz.

Accurate bass does not always sound spectacular, it sounds real. A really good sub will integrate so seamlessly into your system that it will not draw attention to itself.

The cabinet is constructed of 18 mm multi-ply hardwood and coated with scratch free and durable black textured EPDM coating.

Its built-in head base makes it possible to combine with any top-cabinet of your choice. The head base consists of a M10 screw flange speaker adapter.

Two Speakon NL4MP Neutrik connectors are used at the back to ensure that the best possible connections are made.

The second Speakon connector can be used to link more SX412's to each other.

On both sides of the speaker are carry handles provided, to facilitate the transportation.

### ► Specifications

SYSTEM SPECIFICATIONS	
Max power	600 W
RMS power	300 W
Impedance speaker	8 Ohm
Sound pressure 1W/1m	96 dB
Sound pressure Max W/1m	121 dB
Frequency response -3dB	45 Hz - 250 Hz
Frequency range -10dB	40 Hz - 250 Hz
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	380 x 700 x 600 mm
Weight net	40 Kg
Drivers	1 x 12" Subwoofer
Connectors	2 x Speakon NL4MP Neutrik
Construction	Plywood with textured EPDM black coating
Front finish	Open
Carry handles	2 Integrated in the cabinet
Rigging stand fitting	M10 screw flange speaker adapter built in top
Colour	Black
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	42 Kg - 0.23 Cbm
Accessories	Speaker pole flange adapter for 35 mm tubes
<p>*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products</p>	