

► Features

- 15" excursion driver
- Sophisticated control electronics
- Reliable and linear operation
- Integrated M10 screw flange speaker adapter
- Two carry handles for easy transportation
- Scratch-free textured EPDM coating

► Applications

- High power touring applications
- Indoor fixed PA installations
- Clubs
- Theatre
- Broadcast



The AUDAC SX415 is a powerful tandem ported design subwoofer for indoor applications.

To accomplish these needs, AUDAC decided to use a tandem ported design. The results of the carefully designed and tuned subwoofer, are that the SX subwoofers are capable of a high power low frequency sound with exceptionally low distortion levels and a flat frequency response between 45 and 250 Hz and a slide boost on 100 Hz.

This single 15" subwoofer is good for 500 Watt RMS power and 99 dB SPL sensitivity and is capable of a maximum SPL of 126 dB.

Accurate bass does not always sound spectacular, it sounds real. A really good sub will integrate so seamlessly into your system that it will not draw attention to itself.

The cabinet is constructed of 18 mm multi-ply hardwood and coated with scratch free and durable black textured EPDM coating.

Its built-in head base makes it possible to combine with any top-cabinet of your choice. The head base consists of a M10 screw flange speaker adapter.

Two Speakon NL4MP Neutrik connectors are used at the back to ensure that the best possible connections are made.

The second Speakon connector can be used to link more SX415's to each other.

On both sides of the speaker are carry handles provided, to facilitate the transportation.

► Specifications

SYSTEM SPECIFICATIONS	
Max power	1000 W
RMS power	500 W
Impedance speaker	8 Ohm
Sound pressure 1W/1m	99 dB
Sound pressure Max W/1m	126 dB
Frequency response -3dB	45 Hz - 250 Hz
Frequency range -10dB	35 Hz - 250 Hz
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	430 x 800 x 650 mm
Weight net	49 Kg
Drivers	1 x 15" Subwoofer
Connectors	2 x Speakon NL4MP Neutrik
Construction	Plywood with textured EPDM black coating
Front finish	Open
Carry handles	2 Integrated in the cabinet
Rigging stand fitting	M10 screw flange speaker adapter built in top
Colour	Black
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	51 Kg - 0.31 Cbm
Accessories	Speaker pole flange adapter for 35 mm tubes
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products	